

SGP 3330



SGP 3330

Fully automatic strapping machine

High-speed Bundling

Up to 38 bundles per minute to maximize production capacity

Lowest Cost of Ownership

Robust machine design coupled with low maintenance simplicity to minimize costs

Operator-friendly

Intuitive icon-driven controls enable fast bundle set-up

Maximum Uptime

Automatic strap loading, discharging at the end of a coil and refeed technologies minimize downtime for continuous strapping



SGP 3330 / 26 x 20" / 1/4"

Part Number: x66o6oW



The SGP 3330 fully automatic strapping machine provides high speed bundling capacities for packaging lines in various industries and applications. The SGP 3330 is designed to be integrated in conveyor lines and works fully automatic.

The incoming bundle is detected, positioned and strapped according to set parameters on intuitive control panel.

Standard Equipment


- Included strap patterns
 - front strapping
 - double strapping
 - triple strapping
 - multiple strapping
 - centered strapping
 - parallel strapping (front and rear edge)
- Two swivel castors with brakes
- Two fixed castors for easy moving
- Strap loop ejection for cycles without product
- Cycle counter
- Electrical power cable, 5 m
- Energy saving: Automatic conveyor stop, incl. sensor for wake up
- Interface
 - 24 pin Harting connector, incl. mating plug
- Signal lamp 3 colors

Machine Dimensions

Seal method	Heat weld sealing
Electrical supply	100-240 V, 1AC, 47-63 Hz
Room temperature	41-113 °F (5-45 °C)
Cycles per minute up to* (without conveyor)	65/min.
Conveyor speed, stepless	6,5-65 yd/min (6-60 m/min)
Machine weight	660 lbs (300 kg)
Color	Black RAL 9005, slate grey RAL 7015
Arch dimension	26 x 20" (650 x 550 mm)
Packages	
Width / height, min.	4 x 0,4" (100 x 10 mm)
Width / height, max.	25 x 19" (600 x 500 mm)
Length min.	8" (140 mm)
Weight max.	77 lbs (30 kg)
Plastic Strap (PP)	
Strap width	1/4" (5 mm); Part Number: 2X3001
Strap thickness	0,015-0,024" (0,40-0,65 mm)
Strap coil, Ø inside/outside	8/17" (200/430 mm)
Strap tension 1/4 / 1/2" (5-12 mm)	325 N

The polypropylene straps used for the respective applications must correspond with the strap specifications recommended!

*Performance: Depends on arch and package dimensions, conveyor speed, package distances and strap tension.



The company reserves the right to make technical alterations without prior notification.
 © 2024 Signode Industrial Group LLC / ID-10807 / O-240116 / www.Signode.com
 For queries please contact Signode Industrial Group LLC at marketing@signode.com